



# COE-PS-UNIVERSAL | DATASHEET

## Power supply for COE HR AS series cameras



### KEY ADVANTAGES

- Plug and play
- 90-264VAC Input Voltage
- 60 Watts Output Power
- 12VDC  $\pm$ 20% Output Voltage
- >80% Efficiency
- Output Short Circuit Protection
- MTBF > 550,000 hours
- 0 - 50 °C Operating Temperature
- BNC inputs for Trigger in and Strobe out
- Aluminum Case with Mounting Holes



The **COE-PS-UNIVERSAL** is designed to be utilized with COE HR AS models by selecting the appropriate camera power cable.

### SPECIFICATIONS

#### Electrical specifications

Supply voltage	(V, AC)	90-264
Output channels		1
Output voltage	(V, DC)	12
Max output current	(A)	5
Max output power	(W)	60
Power cord		Not included

#### Electrical specifications

Length	(mm)	151.9
Width	(mm)	107.0
Height	(mm)	47.0
Mounting		Free installation

#### Environment

Operating temperature	(°C)	0-50
Storage temperature	(°C)	-40-+85
Operating relative humidity	(%)	10-95, non condensing
Installation		Indoor use only

### COMPATIBLE PRODUCTS

This products is compatible with:

- COE HR AS

### COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.